

12V200Ah

LI-ION BATTERY SPECIFICATION

EnerShare

Enershare Tech Company Limited

www.enersharepower.cn

Address:16th Floor, Huitong Building, No10 Longgang Rd, Longgang Shenzhen, 518116 P.R.C

Li-ion Battery 12V200Ah

Features

- EV-grade safety lifepo4 cells, with lead acid battery shell and built-in BMS.
- 50AH and 100AH can support high rate discharge, max. discharge current can reach200 amp, quick charge within 30mins.
- Can support in series connection to be used in 48 volt systems, can support in parallel connection up to 10 pcs.
- Can support a variety of customization functions, metalhousing, bluetooth (customized IOS APP), heating, LCD display screen, communication (RS485 port/USB port), waterproof.
- Application: solar energy system, solar lighting system, household energy back-up, UPS, RV, Golf Cart, portable device, boat, telecomms.

Application Scenario



Home emergency power supply



Boat



UPS



Telecomms



Li-ion Battery 12V200Ah

Parameters

Datasheet	Rating	Note
Pack Method	4S2P	
Nominal Capacity	200Ah	Discharge: 0.1C Cut-off Voltage:10V Discharge: 0.1C Cut-off Voltage: 10V
Nominal Voltage	12.8V	
Energy	2560Wh	
Charge Voltage	14.6V	
Discharge cut-off voltage	10V	
Charge Method	CC/CV	
Standard Charge Current	15A	
Max. Charge Current	100A	
Standard Discharge Current	20A	
Max. Continues Discharge current	100A	
Cycle Life	2000 times (wk)	Remain capacity:80%
Internal Impedance	≤70mΩ	
Dimension	L521xW238xH220mm	Lead-acid shell
Output Wire	1	
Output Connector	M8 Terminal	
Weight	Approx.22kg	
Working Temperature Range	Charge: 0°C45°C Discharge: -20°C60°C	
Storage Temperature	-10°C50°C	