



- **Ultra-light:** Glass free module is 70% lighter than conventional glass modules
- **Aesthetic:** Seamless integration with underlying installation surface.
- **Durable:** It has passed the durability tests, PID, salt mist and ammonia corrosion tests.

N-HJT Mono-crystalline Flexible PV Module

250W

Electrical Specifications

Module Type		ZJNAC-250F
Peak Power(Pmax)±3%	(W)	250
Power Tolerance	(W)	0~+5
Max.Power Voltage(Vmp)	(V)	34.8
Max.Power Current(Imp)	(A)	7.19
Open-circuit Voltage(Voc)±3%	(V)	40.8
Short-circuit Current(Isc)+3%	(A)	7.6
Module Efficiency	%	20.75

STC: AM1.5, Temperature 25°C, Irradiance 1000 W/m²

Mechanical Specifications

Solar Cells	N-Mono-182*95.8mm
Arrangement	Type-4*15
Front Sheet	ETFE composite membrane
Back Sheet	PET composite membrane
Junction Box	IP67, 2 diodes
Cables	2.5mm² photovoltaic cables
Connectors	MC4 compatible/IP67
Application Class	Class A
Safety Rate	Class II (IEC)
Fire Rate	Class C (TUV)

Packing Configuration

Package Weight & Size	370Kg/pallet & 1560*1125*930mm		
20'GP Container	58 pcs/box	14 boxes/20'GP	812 pcs
40'HQ Container	58 pcs/box	28 boxes/40'HQ	1624 pcs



Product Warranty



Performance Warranty

Dimensions of PV Module

Module Dimensions	1525(±2)*790(±2)*2.5mm
Module Weight	4.4kg(±3%)

Temperature Characteristics & Operating Conditions

Temperature Coefficient (Pmax)	δ[%/°C]	-0.3
Temperature Coefficient (Voc)	β[%/°C]	-0.25
Temperature Coefficient (Isc)	α[%/°C]	+0.045
Nominal Operating Cell Temperature	NMOT	44°C±2°C
Operating Temperature	(°C)	-45~+85
Max. Series Fuse Rating	(A)	15
Max. System Voltage(DC)	(V)	1000 (IEC)

Configuration	Default	Choose
Backsheet Color	☐ White	☒ Black
Cable Length	☒ 600mm	☐ Customization
Connectors	☒ Compatible MC4	☐ Original EVO2



ZHEJIANG NATIVE PRODUCE&ANIMAL BY-PRODUCTS I/E GROUP CO.,LTD
ZHEJIANG G&F FOREIGN TRADING CO.,LTD
Address : No. 308 North Zhongshan Road, Hangzhou, Zhejiang

Tel:+86-0571-85773914
Mob:+86-13705717473
E-mail:yangchuang@zjnac.com
Web:www.zjnac.com

95 mm

105 mm



Energia

MODULO FOTOVOLTAICO



20,8%
Eficiência

250 Wp
Potência

1,20m²
Área

Tecnologia: SILÍCIO MONOCRISTALINO (mono-Si)
Fornecedor: ZHEJIANG G&F FOREIGN TRADING COMPANY LIMITED
Marca: ZJNAC
Modelo: ZJNAC-250F

Mais eficiente



Classe



Menos eficiente

Com base nos resultados do ciclo normalizado pelo Inmetro.



Segurança
Desempenho
Nº de Registro
005 561/2025



Para instruções de instalação e recomendações de uso, leia o manual do aparelho.

16 mm

93 mm

	Energia	MODULO FOTOVOLTAICO		
	PROGRAMA BRASILEIRO DE ETIQUETAGEM	Tecnologia: SILICIO MONOCRISTALINO (mono-Si)		
		Fornecedor: ZHEJIANG G&F FOREIGN TRADING COMPANY LIMITED		
		Marca: ZJNAC		
		Modelo: ZJNAC-250F		Nº de Registro 005 561/2025